

Packing Assemblies



Products

Nylon Stuffing Tubes

Straight

45°

90°

N.P.T

"Y"

Packing Assemblies

Neoprene Plugs

Insulator Discs

Rubber Seals

Submarine Packing Assemblies

Navy Connectors

Electrical Plugs, Receptacles & Covers

Lenses, Globes & Tompions

Casualty Power Supply Terminals

Military Specifications

Corporate Information

Background

Contact

ISO 9001:2015 Certificate

TOP




ASTM Designation F1836M

To obtain a copy of this standard click on the ASTM logo above. Then enter F1836M in the site search box.

For Nylon Stuffing Tubes








MILITARY SPECIFICATION MIL-S-19622

Available in the following sizes: #1, #2, #3, #4 & 4T, #5, #6, #7, #8, #9

Please select a tube size above.



Please select maximum inner diameter "D" of packing bushing that is nearest to the maximum outer diameter "DIA." of the cable or cord being used. Packing bushing I.D. must be equal to or slightly larger than cable maximum O.D.

For use with (but not limited to) cables and cords that meet IEEE-45, IEC 92-3 and US Navy Standards.

Cable & Cord Types

- POWER AND LIGHT COMMUNICATION ELECTRONIC SPECIAL PURPOSE
- CONTROL INSTRUMENTATION TELEPHONE PORTABLE CORDS

Watertight, Non-watertight, Flexing, Non-flexing service.

Dorn Equipment Corporation

27 Upham Street • Melrose, MA 02176 • Tel: 781-662-9300 • Fax: 781-665-0180 • dornequipment.com
© MMXIV Dom Equipment Corporation • Web design by DreamLight.com